



QUANTUM™ 3000

Three-Flavor, Post-Mix Juice Dispenser



FEATURES

- Three product selection
- Easy front loading of concentrate
- High performance peristaltic pumps and a unique mixing valve assure elimination of stratification
- Large concentrate capacity
- Tamper resistant and disposable packaging
- Modular component design provides ease of sanitation and service
- New contemporary cabinet design is a blend of attractive black plastic and sturdy stainless steel
- Easy-to-adjust brixing system controls and maintains a consistent finished drink
- Lighted merchandiser is standard
- Push button or programmable portion controlled dispensing available



Technical Specifications:

DESCRIPTION

Model SLJ1400-3

- 115 volts, 60 Hz, 9.43 amps
- 220 volts, 50 Hz, 5 amps

REFRIGERATION

- 1/3 H.P. hermetically sealed system
- R-134a refrigerant 6.25 oz. (177 g)

CABINETRY

Plastic and stainless steel

DISPENSER DIMENSIONS

Height (with 4" legs) 34 1/2" (87.62 cm)
 Width 14 3/4" (37.50 cm)
 Depth 27 1/4" (69.15 cm)

WEIGHT

Dry weight 129 lbs. (58.56 kg)
 Shipping weight 145 lbs. (65.83 kg)
 Maximum counter weight 161 lbs. (73.09 kg)

RECOMMENDED CLEARANCE

2" (5.08 cm) in back for air circulation

WATER CONNECTION

3/8" (.95 cm) SAE male flare fitting on dispenser

CONCENTRATE STORAGE

640 oz. (18.9 L)

WATER SUPPLY REQUIREMENTS

- 80 psi (5.6 kg/sq. cm) maximum static pressure
- 20 psi (1.4 kg/sq. cm) minimum dynamic pressure

COOLING CAPACITY

Continuous 5 oz. (147.85 ml) drinks at 4 per minute with 75°F (24°C) concentrate without exceeding 45°F (7°C) drink temperature

FLOW RATE

Adjustable water flow rate from 1.6 oz./sec. (47.31 ml/sec.) to 2.2 oz./sec. (65.05 ml/sec.); handles 2 + 1 through 7 + 1 concentrate

OPTIONAL ACCESSORIES

- Illuminated merchandiser
- Electric hospital hose
- Portion control
- Sanitizing tank kit
- Dispense key lock
- Extended splash panel kit (lowers drink tray)

AGENCY LISTINGS

